



Black Gator® Wireline Logging Plug



The Black Gator® Wireline Logging Plug allows wireline intervention tools to be suspended below the Electric Submersible Pump (ESP) bypass system via the bypass tubing. This allows for work under both static and dynamic conditions.

The Wireline Plug is seated into the Bypass Nipple using a Wireline Plug Hammer attached to the wireline string. The Wireline Plug Hammer has grapple inserts to secure it to the wireline cable.

FEATURES

- Compact design
- Optional tool catcher
- Jar up with wireline hammer to set
- Pull up with PLT to release
- 2.312", 2.562", 2.750", 2.812" sizes for nipples
- 1.375" external fish neck
- Dress kit to change nipple sizes (standard base unit design)
- Top NO-GO design
- Pressure equalizing feature allows easy retrieval
- No shear pins to redress

SPECIFICATIONS

- 13Cr material with QPQ finish
- 5,000 psi MWP
- Up to 350° F
- Viton® or Aflas® seals as standard

Flow Tube Part Number	Wireline/Slickline Diameter (in.)
-----------------------	-----------------------------------

WLP-0002-01	0.082
WLP-0002-02	0.092
WLP-0002-03	0.108
WLP-0002-04	0.125
WLP-0002-05	0.1875
WLP-0002-06	0.218
WLP-0002-07	0.226
WLP-0002-08	0.235
WLP-0002-09	0.250
WLP-0002-10	0.312
WLP-0002-11	0.320
WLP-0002-12	0.460
WLP-0002-13	0.469

Wireline Plug Part Number	NO-GO Diameter (in.)	Seal Diameter (in.)
---------------------------	----------------------	---------------------

WLP-2312-TNG-01	2.350	2.312
WLP-2562-TNG-01	2.610	2.562
WLP-2750-TNG-01	2.800	2.750
WLP-2812-TNG-01	2.865	2.812